



US10-ID/HID/M



US10-B/MAG



US10-C

US10 Series

Choice of Barcode, Mag Stripe, Proximity or Fingerprint Reader

... all in the same design!



US10 series is innovative versatile time clocks which combine a highly durable yet elegant casing with a variety of identification methods from bar code cards, magnetic stripe cards, RFID/proximity cards and/or fingerprints.

US10 installs easily on your network and supports both hard-wired TCP/IP and optional wireless connections. The standard RS-232 ports lets users connect directly to PC and USB host allows user to download data using USB Flash Disk drive.

US10 Series comes with stunning 3" color TFT color screen for beautiful display of graphics, icons and photos. It also has 4 additional functions key to customize the reader for special requirements (i.e. break in/out recording, job code entry, tip entry, etc.). Managers can even leave SMS messages behind for employees reporting in/out of work.

Additionally, with built-in scheduler and relay contact US10 can even ring an external bell to signify the start and close of work shift(s).

Sleek, versatile, rugged and accurate . . . ALL IN THE SAME DESIGN!

Features

- Colorful TFT graphical interface for ease of use
- Rugged and highly accurate ZK optical sensor
- Rugged 20-key keypad with four programmable function keys
- USB host port for easy data transfer to a USB flash drive
- Relay contacts for access control/external bell function
- Serial port can be used for communication with reader or for attaching a printer
- Optional WiFi connectivity allows for easy and hassle free installation over a wireless network
- Audio and Visual feedback for accepted and rejected swipes
- Multi-language firmware supports English, Spanish & French
- Included mounting plate is designed to fit standard US double gang box
- SDK available for OEM customers and software developers

Configuration



Specifications

Capacity

- Fingerprints: 1,500 templates
- Cards: 10,000 transactions
- Transactions: 50,000

Display

- 3" TFT color LCD screen

Communication

- RS232/485
- Ethernet
- USB-Host
- WiFi (optional)

Standard Functions

- Daylight Savings Time
- Automatic Status Switch
- Scheduled bell

Power

- Power Supply: 12V DC, 1.5A

Environment

- Operating Temp: 32-113 °F (0-45 °C)
- Operating Humidity: 20% to 80%

Dimensions

- Height: 6.5" (16.5 cm)
- Width: 5.5" (14 cm)
- Depth: 1.8" (5 cm)

Packaging Dimensions

- Box: 9" x 10 1/2" x 3 1/2"
- Weight: 3 lbs (48 ozs.)

