



Door release buttons K1-1/K1-2

Features

- ✓ No touch / Touch free Exit Sensor (Diffused Detection)
- ✓ Optical / Infrared Technology
- ✓ IP-55 Ingress Protection / SUS 304 Stainless steel Plate
- ✓ User friendly (Healthy protection)
- ✓ Free from contagious diseases spread
- ✓ Detection range: 0.1 ~ 10 cm
- ✓ Application: Gate/Door/Exit/Automation control
- ✓ High capacity of relay dry contact (3A/AC120V,DC30V)
- ✓ Normally open/Normally close/Common relay output
- ✓ Twin led indicators for sensor standby or approached :
 - Sensor Standby: BLUE LED ON
 - Visitors whom approached to the sensor in 10 cm : RED LED ON
- ✓ K1-1 (One relay) / K1-2 (Two relays)



Specifications

<u>Contact Rating:</u>	3A/AC120V, DC30V
<u>Input Volt.</u>	DC 12V
<u>Management</u>	Simple and clear for operation.
<u>Operation temperature range</u>	20°C 55°C

<u>Life</u>	100,000 Times
<u>Mounting</u>	Durable stainless steel plate
<u>Dimension</u>	115x70x29(mm)
<u>Weight</u>	85g

Connectivity diagram

