



## S160-C / S260-C

### Product Description

S160-C / S260 is a Time & Attendance terminal with incorporated proximity reader with 3" TFT display. Easy to install, and with a modern design, it is the perfect solution for small installations. The color TFT display offer users easy menu management. It can connect to Time & Attendance management software by Ethernet or USB port, and also operate on standalone mode, downloading data by USB pendrive.

#### Standard functions



#### Optional functions



## Features

- ✓ Time and Attendance device
- ✓ Incorporates EM reader and optional Mifare, HID, etc..
- ✓ Stores up to 30000 users and cards.
- ✓ Stores up to 50.000 log records without PC download.
- ✓ Allows communication with PC through Ethernet and USB port
- ✓ Events management (doctor, personal issues, etc...)
- ✓ Multi-language in text and audio



## Specifications

### Capacity

ID Card Capacity	30,000
Log Capacity	100,000

### Hardware

Platform	ZEM510
CPU	32bit MultiBio Microprocessor 400MHz
Memory	32M RAM, 256M Flash

### Display

LCD	TFT Screen 3 inch
LED Indicator	Red / Green

### Environment

Oper. Temp	0°-45°C
Oper. Humidity	20%-80%

### Power

Power	5V, DC 2A
-------	-----------

### Communication

Comm. Port	Ethernet, USB-Client
Pen drive	USB-host

### Proximity Module

Type	EM card
Identification	<=1 seconds

### Languages

Available	All European languages
Maximum	7
Voices	Allowed

### Keypad

Type	buttons keypad
Function Keys	6 defined by user
Events Management	Up to 9999 with description

### Dimensions

Dimensions	192x137x45mm (L x W x D)
Weight	1.02Kg

### Firmware

O.S	Linux
Applications	T&A
SDK	Standalone SDK

## Connectivity diagram

